

FLIP FLAP DOOR

Flip Flap Doors by Metaflex are the perfect answer when it comes to the reliable solution for hygienic areas room closure system. Build from high class materials with optimum level of engineering, these doors meets the important criteria for workflow optimization.

Mak Flip Flap Swing doors not only allows you to pass through quickly but also with absolute hygiene.

Mak Flip Flap swing doors provide ease of usage with relieve from troublesome maintenance. The two way hinges provides the flexibility of opening at both sides with the option of 90° stay, enabling the optimum utilization of the space and hence making them user friendly.

Mak Flip Flap swing doors are distinctively designed for an array of usage areas, wherever cleanliness and hygiene maintenance is of utmost importance. These doors are perfect for places like food processing industry, fisheries, hospitality and other hygiene oriented areas. Their ease of operation and minimal maintenance makes them the highly desirable product for the consumers.

These doors are easy to clean; as a result, they ensure the absolute hygiene levels and a long functional life, even at the places of high traffic and stress. Mak Flip Flap swing doors are available in variety of materials and finishes, which makes them robust enough to cater a wide range of application areas with right solution.

OTHER DESIGN FEATURES & BENEFITS:

- ❖ 40mm thick door leaf with CFC free foam core.
- ❖ Door leaf available in Stainless Steel and PCGI (RAL 9002).
- ❖ Windows are available in variants of Double glaze flush view port and Acrylic with PVC frame.
- ❖ Pivot pin, hinges made of non-rusting stainless steel (SS 304).

KEY BENEFITS:

- ❖ High resistance to impact
- ❖ Resistant to fats, solvents and acids
- ❖ Perfect hygiene
- ❖ Food safe due to SS 304 door leaf
- ❖ Corrosion protected return mechanism
- ❖ Maintenance free
- ❖ Highly durable



DESIGN FEATURES:

| | | |
|---|-----------------------------|---|
| 1 | Door leaf | <ul style="list-style-type: none">• Single leaf• Double leaf |
| | Leaf thickness | <ul style="list-style-type: none">• 40mm PU foam filled (CFC free) |
| | Leaf surface | <ul style="list-style-type: none">• SS 304, 0.8mm thick• PCGI, 0.8mm thick |
| | Finish variants | <ul style="list-style-type: none">• SS with options of circle brush and matt finishes.• PCGI in RAL 9002. |
| 2 | Frame | <ul style="list-style-type: none">• SS 304, 2mm thick• Galvanized steel powder coated, 2mm thick. |
| 3 | Installation variants | <ul style="list-style-type: none">• For installation in masonry• For installation in panels |
| 4 | Window | <ul style="list-style-type: none">• Double glaze flush view port of 300x300mm, with option of other sizes (on request).• Acrylic view port with PVC frame of 348x638mm |
| 5 | Hinges | <ul style="list-style-type: none">• Stainless steel hinges with integrated 90° stay |
| 6 | On demand options available | <ol style="list-style-type: none">1. Crash Guard:<ol style="list-style-type: none">I.1. Engineering plastic, 150mm wide and 10mm thick.I.2. Polyester reinforce PVC strap, 200mm wide and 3mm thick.2. Kick plate:<ol style="list-style-type: none">I.1. SS 304, 0.8mm thick with 200mm height. |
| 7 | Sizes Available (in mm) | <ol style="list-style-type: none">1. Single leaf:<ol style="list-style-type: none">I.1. Minimum- 700x1800I.2. Maximum- 1100x24002. Double-leaf:<ol style="list-style-type: none">I.1. Minimum- 1500x2100I.2. Maximum- 2200x2400 |



Metaflex Doors India Pvt. Ltd.

REGIONAL OFFICE: Mumbai: Office No.709, Thacker Tower, Plot No.86, Sector 17, Vashi, Navi Mumbai 400 705

Bangalore: 716/966/2, 9th Main Road, 7th Sector, H.S.R Layout, Bangalore 560 102

CORPORATE OFFICE: 8A, Udyog Vihar Part I & II, Greater Noida- 201306 U.P.

Ph: +91-120-4751000 | Fax: +91-120-4751026 | www.metaflexdoors.in